



**ENERGY**  
EDO  
EDO777284

A  
B  
C  
D  
E  
F  
G

**C**

**30**  
kWh/1000h

2019/2015

30w  
4100 lm  
4000K  
220-240 V AC  
50-60Hz  
110°  
IP65  
IK06

## Floodlight MODAN LED 30 W

The MODAN floodlights are a choice for a long time. The housing is made of aluminum and tempered glass, which gives a high degree of protection IP65. It has a versatile bracket, thanks to which it can be freely adjusted and mounted. They are perfect for lighting buildings, gates, gardens or facades.

SPECIFICATIONS	EDO777284
Source Type:	Floodlight LED
Application:	inside/outside
Installation:	surface
Adjustable:	yes
Dimensions [mm]:	
- height [mm]:	204.5mm
- width [mm]:	165mm
- depth [mm]:	46mm
Colour:	black
Material:	aluminium, glass
Cover colour:	milky
Energy efficiency class [A-G]:	<b>A</b> <b>C</b>
Cooperation with a dimmer:	no
Sensor:	-

TECHNICAL DATA	
Power in the on-mode P <sub>on</sub> [W]:	30 W
Standby power P <sub>sb</sub> /P <sub>net</sub> [W]:	-
Rated voltage [V]:	220-240 V AC
Rated frequency [Hz]:	50-60 Hz
Color temperature [K]:	4000 K
Light color change:	no
Lighting angle [°]:	110°
Color rendering index CRI:	≥70
Color rendering index R9:	12
Useful luminous flux [lm]:	4100 lm
Light distribution angle [°]:	wide cone (120°)
Luminous efficiency [lm/W]:	161,27 lm/W
Rated life [h]:	25000 h
Number of cycles on/off:	15000
On-mode energy consumption [kWh/1000h]:	30kWh/1000h
IP:	IP65
IK:	IK06
Klasa ochronności:	I
Mercury content:	no
Environmental conditions:	-20°C...40°C

LOGISTIC DATA	
Collective packaging [pc.]:	20pc.
Weight [g]:	624g
EAN:	

