## MALGA 1 Black





















0

## Lighting fixture MALGA 1 Black

MALGA surface-mounted luminaires are an ideal alternative to rail lighting. The modern, simple base is combined with oblong tube reflectors. The freedom to adjust the angle of incidence of light, each spot separately gives the opportunity to illuminate and focus attention on a specific element of the space arrangement, moreover, they will be perfect as the main lighting when using GU10 light sources with more power.

| SPECIFICATIONS                                    | ED0777347          |
|---|--------------------|
| Application:                                      | inside             |
| Type of assembly:                                 | surface-mounted    |
| Instalation site:                                 | ceiling            |
| Connection type:                                  | screw cube         |
| Colour:   | black              |
| Type of finish:                                   | sandblasted        |
| Material:   | aluminium          |
| Dimensions:                                       |                    |
| -basis [mm]:                                      | 55x55x26mm         |
| -lampshade [mm]:                                  | 55x100mm           |
| -overall height [mm]:                             | 170mm              |
| -total lenght [mm]:                               | 55mm               |
| -mounting bolt distance [mm]:                     | 28mm               |
| Adjustable:                                       | yes                |
| Shutter:  | -                  |
| Socket included:                                  | yes                |
| Socket type:                                      | GU10               |
| Number of slots:                                  | 1                  |
| Light source included:                            | no                 |
| TECHNICAL DATA                                    |                    |
| Maximum power [w]:                                | 35W                |
| Rated voltage [v]:                                | 220-240 V AC       |
| Rated frequency [Hz]:                             | 50-60 Hz           |
| IP:   | IP20               |
| Protection class:                                 | I                  |
| Mercury content:                                  | no                 |
| Environmental conditions [°c]:                    | -2050°C            |
| The minimum distance from illuminated object [m]: | 0,5m               |
| LOGISTIC DATA                                     |                    |
| Collective packaging [pc.]:                       | 50pc               |
| Weight [g]:                                       | 195g               |
| Weight with packaging [g]:                        | 233g               |
| EAN:  | 5  903943  4891 90 |

