

ZORAN LED 50W



EDO777678



Floodlight ZORAN LED 50W

SPECIFICATIONS	EDO777678
Source type:	LED floodlight
Application:	indoor/outdoor
Type of assembly:	surface-mounted
Adjustable:	yes
Dimensions [mm]:	
-height [mm]:	185mm
-width [mm]:	210mm
-depth [mm]:	45mm
Colour:	black
Material:	aluminium, glass
Lampshade:	milky
Energy efficiency class [A-G]:	F
Cooperation with a dimmer:	no
Sensor:	no
TECHNICAL DATA	
Power in the on-mode P_{on} [W]:	50W
Standby power P_{sb}/P_{net} [W]:	-
Rated voltage [V]:	220-240V
Rated frequency [Hz]:	50 Hz
Color temperature [K]:	4000K
Light color change:	no
Light distribution angle [°]:	120°
Color rendering index CRI:	Ra70
Color rendering index R9:	8
Useful luminous flux [lm]:	4280lm
Measurement of the luminous flux in [°]:	cone (120°)
Rated life [h]:	25000h
Number of cycles on/off:	15000
IP:	IP65
IK:	IK05
Protection class:	I
Mercury content:	no
Environmental conditions [°C]:	-20°C...40°C
LOGISTIC DATA	
Collective packaging [pcs.]:	20pcs.
Weight [g]:	572g
Weight with packaging:	644g
EAN:	



ENERGY

EDO
EDO777678

A

B

C

D

E

F

G

F

50
kWh/1000h

2019/2015

50W

4280 lm

4000K

220-240 V AC
50-60Hz

120°

IP65

IK05

